

1. Unique identification code of the product type:
**Dry-pressed ceramic tiles with a low water absorption rate $0,5\% < E \leq 3\%$
EN 14 411:2012 Bl_b attachment H, Floor tiles – GL, UGL**
2. Intended use(s):
For fixing on interior and/or exterior floors, including stairs, in buildings and industrial plants
3. Manufacturer:
**CERRAD Sp. z o.o.
ul. Radomska 49B
27-200 Starachowice**
4. System(s) of assessment and verification of constancy of performance: **System 4**
5. Harmonized standard: **EN 14 411:2012**
6. Notified body(ies): **NA – not applicable**
7. Declared performances:

Technical performance:		
Key properties	Performances	Harmonized technical specification
Reaction to fire	Class A1 _{FL}	EN 14 411:2012
Release of hazardous substances:		
- Cadmium	< 0,07 mg/dm ²	
- Lead	< 0,8 mg/dm ²	
Breaking strength	≥1100 N	
Anti-slip properties – CEN/TS 16165:2012, att. B; DIN 51130	≤ R13	

Performances of the product described above meet the declared performances. This declaration of performance is issued in accordance with the regulation (EU) no 305/2011 under the sole responsibility of the manufacturer indicated above.

On behalf of the manufacturer:
Dawid Ceglowski – Chief Operating Officer

CZŁONEK ZARZĄDU

Dawid Ceglowski

Paweł Smolarek – Chief Product Officer

CZŁONEK ZARZĄDU

Paweł Smolarek

Starachowice, 13.03.2020