

# UK DECLARATION OF CONFORMITY

No. 8.1/01



1. The unique identification code of the product type:

**Dry- pressed ceramic tiles with low water absorption  $E_b \leq 0.5\%$ ; Groupe BI<sub>a</sub>, Glazed (GL)**

2. Intended use or uses:

**For internal and /or external floors, including stairs, in buildings and industrial facilities**

3. Manufacturer:

**CERRAD Ltd.  
27-200 Starachowice  
Radomska 49B Str.**

4. System(s) of assessment and verification of constancy of performance: **System 4**

5. Harmonised standard: **BS EN 14411:2012**

6. Notified body or bodies: **Not applicable**

7. Declared performance

Essential characteristics		Performance
Reaction to fire		A1 <sub>FL</sub>
Release of dangerous substances:		
- Cadmium		$\leq 0,07 \text{ mg/dm}^2$
- Lead		$\leq 0,8 \text{ mg/dm}^2$
- Others		NPD
Breaking strength	thickness $\geq 7,5 \text{ mm}$	$\geq 1300 \text{ N}$
Slipperiness		NPD
Bond strength/adhesion:		
- cementitious adhesives		NPD
- dispersion adhesives		NPD
- reaction resin adhesives		NPD
- mortar		NPD
Thermal shock resistance		Pass
Durability for:		
- internal use:		Pass
- external use: resistance to freeze-thaw cycles		Pass
Tactility		NPD

The performance of the product(s) identified above is/are in conformity with the declared performance in the table above.  
The declaration of conformity is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Magdalena Widulińska**

Kierownik Działu Technologicznego

*Widulińska Magdalena*

in Starachowice, 02.01.2025