

DECLARATION OF PERFORMANCE No. 3/04 CPR

1. Unique product type identification code:
**Dry-pressed ceramic tiles with a low water absorption rate $0,5\% < E \leq 3\%$
EN 14 411:2012 B1_b attachment H, Facade stone – GL, UGL**
2. Intended use or uses:
For fixing on interior and/or exterior walls, in buildings and industrial plants
3. Manufacturer: **CERRAD Sp. z o.o.
ul. Radomska 49B
27-200 Starachowice**
4. System(s) for evaluation and verification of performance characteristics: **System 4**
5. Harmonized standard: **EN 14 411:2012**
6. Notified Unit(s): **NA – not applicable**
7. Performance declared:


Main characteristics	Performance characteristics	Harmonised technical specification
Reaction to fire	Class A1	EN 14 411:2012
Hazardous substance release:		
- Cadmium	$< 0,07 \text{ mg/dm}^2$	
- Lead	$< 0,8 \text{ mg/dm}^2$	
Bonding/adhesion strength		
- cement based adhesives – PN-EN 1348:2008; C2	$\geq 0,5 \text{ N/mm}^2$	
- dispersion adhesives – PN-EN 1324:2008; D1	$\geq 1,0 \text{ N/mm}^2$	
- epoxy resin based adhesives – PN-EN 12003:2010; R1	$\geq 2,0 \text{ N/mm}^2$	

The performance characteristics of the aforementioned product comply with the set of declared performance properties. This Declaration of Performance has been issued pursuant to the Regulation (EU) 305/2011 on the sole responsibility of the manufacturer indicated above.

Signed on behalf of the manufacturer:p

Dawid Ceglowski – Chief Operating Officer

Paweł Smolarek – Chief Product Officer

CZŁONEK ZARZĄDU

 Dawid Ceglowski

CZŁONEK ZARZĄDU

 Paweł Smolarek

Starachowice, 13.03.2020