

DECLARATION OF PERFORMANCE

No. 4/05 CPR

1. Unique product type identification code:
Dry-pressed ceramic tiles with a low water absorption rate $0,5\% < E \leq 3\%$
EN 14 411:2012 B1₁ attachment H, Universal tiles – GL, UGL
2. Intended use or uses:
For fixing on interior and/or exterior walls, interior and/or exterior floors, including stairs, in buildings and industrial plants
3. Manufacturer:
CERRAD Sp. z o.o.
ul. Radomska 49B
27-200 Starachowice
4. System(s) for evaluation and verification of performance characteristics: **System 4**
5. Harmonized standard: **EN 14 411:2012**
6. Notified Unit(s): **NA – not applicable**
7. Performance declared:

Main characteristics	Performance characteristics	Harmonised technical specification
Reaction to fire	Class A1/A1 _{FL}	EN 14 411:2012
Hazardous substance release:		
- Cadmium	< 0,07 mg/dm ²	
- Lead	< 0,8 mg/dm ²	
Bonding/adhesion strength		
- cement based adhesives – PN-EN 1348:2008; C2	≥ 0,5 N/mm ²	
- dispersion adhesives – PN-EN 1324:2008; D1	≥ 1,0 N/mm ²	
- epoxy resin based adhesives – PN-EN 12003:2010; R1	≥ 2,0 N/mm ²	
Breaking force	≥ 1100 N	
Slip – CEN/TS 16165:2012, att. B; DIN 51130	≤ R13	

The performance characteristics of the aforementioned product comply with the set of declared performance properties. This Performance Declaration has been issued pursuant to the Regulation (EU) 305/2011 on the sole responsibility of the manufacturer indicated above.

Signed on behalf of the manufacturer:

Dawid Ceglowski – Chief Operating Officer

Paweł Smolarek – Chief Product Officer

CZŁONEK ZARZĄDU
Dawid Ceglowski
Dawid Ceglowski

CZŁONEK ZARZĄDU
Paweł Smolarek
Paweł Smolarek

Starachowice, 13.03.2020