

DECLARATION OF PERFORMANCE

Nr 7A/02 CPR

1. Unique product type identification code:
**Dry-pressed ceramic tiles with a low water absorption rate $E \leq 0,5\%$
EN 14 411B₁, attachment G, Universal tiles – GL**
2. Intended uses:
For interior and/or exterior walls, interior and/or exterior floors, including stairs, in buildings and industrial plants
3. Manufacturer:
**CERRAD Sp. z o.o.
ul. Radomska 49B
27-200 Starachowice**
4. System(s) for evaluation and verification of performance characteristics: **System 4**
5. Harmonized standard: **PN EN 14411:2013-04**
6. Notified Unit(s): **Not applicable**
7. Performance declared:

Essential characteristics		Performance characteristics	Harmonised technical specification
Reaction to fire		Class A1/A1 _{FL}	PN EN 14411:2013-04
Release of dangerous substances:			
- Cadmium		< 0,07 mg/dm ²	
- Lead		< 0,8 mg/dm ²	
Breaking strenght	Thickness ≥ 7.5 mm	≥ 1300 N	
	Thickness < 7.5 mm	≥ 700 N	
Slipperiness – CEN/TS 16165:2012 Attachment B; DIN 51130		R9	
Bonding/adhesion strength: - cementitious adhesives - dispersion adhesives - reaction resin adhesives		≥ 0,5 [N/mm ²] ≥ 1,0 [N/mm ²] ≥ 2,0 [N/mm ²]	
Durability for:			
- Internal uses:		Complies	
- External uses: freeze thaw resistance			
Thermal shock resistance		Complies	
Tactility		NPD (no performance determined)	

The performance characteristics of the aforementioned product comply with the set of declared performance properties. This Performance Declaration has been issued pursuant to the Regulation (EU) 305/2011 on the sole responsibility of the manufacturer indicated above.

Signed on behalf of the manufacturer:

Dawid Cegłowski - Chief Operating Officer

Paweł Smolarek - Chief Product Officer

CZŁONEK ZARZĄDU

Dawid Cegłowski
Dawid Cegłowski

CZŁONEK ZARZĄDU

Paweł Smolarek
Paweł Smolarek

Starachowice, 03.06.2019