

## DECLARATION OF PERFORMANCE

### Nr 8C/02 CPR

1. Unique product type identification code:  
**Dry-pressed ceramic tiles with a low water absorption rate  $E \leq 0,5\%$**   
**EN 14 411B<sub>1</sub> attachment G, Floor tiles – GL**
2. Intended uses:  
**For interior and/or exterior floors, including stairs, in buildings and industrial plants**
3. Manufacturer:  
**CERRAD Sp. z o.o.**  
**ul. Radomska 49B**  
**27-200 Starachowice**
4. System(s) for evaluation and verification of performance characteristics: **System 4**
5. Harmonized standard: **PN EN 14411:2013-04**
6. Notified Unit(s): **Not applicable**
7. Performance declared:

Essential characteristics		Performance characteristics	Harmonised technical specification
Reaction to fire		Class A1 <sub>FL</sub>	PN EN 14411:2013-04
Release of dangerous substances:			
- Cadmium		< 0,07 mg/dm <sup>2</sup>	
- Lead		< 0,8 mg/dm <sup>2</sup>	
Breaking strenght	Thickness ≥7.5 mm	≥ 1300 N	
	Thickness < 7.5 mm	≥ 700 N	
Slipperiness – CEN/TS 16165:2012 Attachment B; DIN 51130		R11	
Durability for:			
-Internal uses:		Complies	
- External uses: freeze thaw resistance			
Tactility		NPD (no performance determined)	

The performance characteristics of the aforementioned product comply with the set of declared performance properties. This Performance Declaration has been issued pursuant to the Regulation (EU) 305/2011 on the sole responsibility of the manufacturer indicated above.

Signed on behalf of the manufacturer:

-  -

Dawid Cegłowski - Chief Operating Officer

Paweł Smolarek - Chief Product Officer

**CZŁONEK ZARZĄDU**

*Dawid Cegłowski*  
**Dawid Cegłowski**

**CZŁONEK ZARZĄDU**

*Paweł Smolarek*  
**Paweł Smolarek**

Starachowice, 03.06.2019